

SEAL CLEAN WATERPROOF KEYBOARD INTERNATIONAL LAYOUT

Model: SSKSV208xx, SSWKSV208xx

Seal Clean Waterproof Keyboards with an International layout from Seal Shield. Available in a range of international languages. Keyboards have a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. True type keyboard with tactile feel and full travel keys for smooth and natural typing. Features a Quick Connect Cable with RF shielding and a Seal Cap™ for easy plug-and-play. Features a full-size numeric keypad for added convenience.

FEATURES:



100% Waterproof,
Dishwasher-Safe,
& Fully Submersible



Gold Coated USB
Quick Connect Cable,
RF Shielding, & Seal
Cap™ Protector



Available in a Range
of International Languages



Full-Size Numeric
Keypad and Laser
Etched Keycaps



Designed to Withstand
Industrial-Grade Disinfectants
& Cleaners



IP68-Certified



Standard Style Keyboard
for Smooth Typing



ABS Plastic with
Stainless Steel Screws
& Non-Corrosive Components



SSKSV208xx



SSWKSV208xx

ADVANCED CLEANING CAPABILITIES

- Dishwasher-Safe
- Compatible with Spray & Wipe Disinfectant Products:
 - Clorox Healthcare®
 - Lysol®
 - PDI Products
 - Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants



SEAL CLEAN WATERPROOF KEYBOARD

INTERNATIONAL LAYOUT

Model: SSKSV208xx, SSWKSV208xx

TECHNICAL DATA:

Compatibility:	Windows®
Construction:	ABS Plastic (Standard Style)
Key Layout:	105 (International Layout)
Net Dimensions L x W x H:	45.9 x 17.4 x 3.5cm
Gross Dimensions L x W x H:	47.6 x 19.7 x 4.45cm
Net Weight:	1.93 lb (0.875 kg)
Gross Weight:	2.315 lb (1.050 kg)
Cable Length:	15cm Quick Connect Cable with 1.83m USB Cable
Connection Type:	Gold Plated USB (can support PS/2 technology)
Key Switch Force:	53 ± 7 gf
Key Switch Life Cycle:	Greater than 10 Million Keystrokes
Key Switch Type:	Membrane Key Switch with Tactile Feedback
Keycaps Imaging Type:	Laser Etched
Operating Current:	60mA
Total Key Travel:	4.0 ± 0.2 mm
Operating Voltage:	5VDC
Storage Temperature:	-5° - 140° F (-20° to 60° C)
EMI - RFI:	Conforms to FCC Rules for Class B Device
Waterproof/Dustproof Ratings:	IP68, NEMA 4X
Approvals/Certifications:	RoHS, WEEE, CE, FCC, WHQL, ICES-003, cULus, EAC, KC, RCM, REACH, Cal Prop 65



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty